

## GS3-200 Filtration System



### Construction:

Cabinet: Brushed stainless steel to IP56 compliance  
Baffled – sound attenuated  
Sound Level: 59 dbA  
Dimensions: 35" x 23" x 20"  
Weight: 134 lbs.

### Blowers:

Performance: 210 CFM@ 39" wc  
Centrifugal - direct-drive, brushless motor  
20,000 + hr mtbf

### Electrics/Controls:

90 - 250 1/50-60  
Digital Graphic Display  
- Electronic variable speed blower control  
- Calibrated electronic VOC /gas sensor  
Pre-wired 3 wire power cable, 7.5 ft w/  
plug

Amp Draw: 15.0 / 8.0

### Standard Equipment

Standard Filter Set  
Digital Graphic Display/Controls  
3", 4" or 6" inlet  
8' - 2 ply smooth-core rubber hose  
(4) Industrial grade wheels – 2 locking  
Installation guide / Operations manual

### Standard Filter Set

Pre-Filter  
(3) Gas / Odor Filters

Model	Description	\$\$\$ USD
GS3-200	Stainless Steel - 200 cfm - 230/1/50-60	\$ 3790.00
FA227	Remote Interface	\$ 91.00
Part #	Options / Spares	
FA540B	Pre-Filter	\$ 117.00
FA501D	Gas / Odor Filter	\$253.00 each

Fumex Inc.  
1150 Cobb International Place Kennesaw, GA 30152  
[www.fumexinc.com](http://www.fumexinc.com)  
800-432-7550