


# Model FA2-E (stainless Steel)



## Air Filtration system Series

The Fumex FA2-E fume extractor utilizes a high performance 3 stage hybrid air filter system to capture and treat air pollutants generated during laser engraving processes. Operator friendly digital controls and integrated electronic gas sensor continuously monitor the system performance and display operating parameters on the high-visibility LED screen. Large capacity inexpensive pre-filters extend filter change intervals and protects the large HEPA filter and gas/odor filter offering an extremely cost-effective, efficient laser engraver fume extractor system. High performance variable speed blower provides maximum application flexibility. Ideal for medium to heavy duty laser engraving applications.





#### **Construction:**

- ► Cabinet: 304 grade Brushed stainless steel to IP56 compliance
- ► Baffled sound attenuated
- ➤ Sound Level: 60 dbA
- ➤ Weight: 101 lbs. / 46 kg.

#### **Blowers:**

- ► Performance: 266 cfm @ 39" wc
- ► Variable speed blower
- Centrifugal direct-drive, brushless motor
- Rated 20,000 hour + mtbf

#### **Electrics/Controls:**

- 90/250/1/50-60 (120v or 240v plug)
- ► Digital display with variable speed blower
- > Pre-wired 3 wire power cable, 9 ft. with plug
- ► Digital Controls
- Electronic variable speed blower control
- Electronic individual filter monitoring with display
- Calibrated electronic VOC gas sensor
- ► Electronic digital interface relay for two-way communication, filter monitoring and remote start/stop control
- Amp draw to 12.0 (120v) or 8.0 (240v)

### **Standard Filter Set:**

- ▶ 10" Pre-Filter: o Large capacity box style o 99% efficient @ 1.0 micron
  - o Deep-pleated dimpled media
- ► 6" HEPA Filter: o 99.97% efficient @ 0.3 micron
- ► 6" Gas / Odor Filter:
  - o Large capacity gas/odor filter
  - o Provides broad spectrum gas/odor control
  - o Dustless construction suitable for all environments
  - o Bonded carbon technology maximizes one pass efficiency


### **Standard Equipment:**

- ► UL, ULC and CE/TUV compliance available
- ► 8 ft. 2-ply ribbed rubber hose
- > 2", 3" or 4" inlet diameter hose with clamps
- ► Digital graphic controls
- ► (4) Industrial grade wheels two locking
- Installation guide / Operations manual

## **TECHNICAL DATA**



- Programable via USB port pressure set points, blower speeds, and VOC detection
- High visibility Graphic display indicating blower speed, filter, and unit system status
- System Data logging: monitoring blower usage, filter service intervals accessed by USB port





#### **Source Capture Arms and Hoods**



Terms: Net 30 days with approved credit FOB POINT: Kennesaw (Atlanta), GA **FUMEX ACCESSORIES** 

# FA151 (Bench Hood)

**Additional Application Accessories** 





FB1 (External High-Capacity Pre-filter)

 FUMEX | 1150 Cobb International Place Kennesaw, GA 30152

 770-514-7907 | 800-432-7550 (toll) | www.fumexinc.com

