

The Fumex-DT (desktop) is a quiet, low cost, highly efficient fume extraction system designed to capture and filter the fumes generated in a variety of processes. Simple to use and operate the system incorporates intelligent controls, filter monitoring, variable speed airflow and easy interface / connectivity. The Fumex DT can be fitted with a standard 3 stage filter incorporating HEPA and Gas/Odor filtration or specialty application specific medias. The compact size and simplicity of design is ideal for the following applications.



Laser Engraving



Select Laser Sintering



Soldering Hobbyists



3D Printing



Multi-Jet Modeling



Dental



Direct Digital Manufacturing 3DP



SLA



3DP



Construction:

- Cabinet: 16 ga. welded steel, powder coat finish
- Baffled – sound attenuated
- Sound Level: 55 dbA
- Weight: 25 lbs.

Blower Motor:

- Performance: 105 cfm
- Variable speed blower
- Centrifugal - direct-drive, brushless motor
- Rated 20,000 hour + mtbf

Electrics/Controls:

- 100-130/1/50-60 (120-volt plug)
- Digital display with variable speed blower
- Pre-wired 3 wire power cable, 9 ft. with plug
- Digital Controls
 - Electronic variable speed blower control
 - High visibility LED filter indicator
- Calibrated electronic VOC gas sensor
- Electronic digital interface relay for two-way communication, filter monitoring and remote start/stop control
- Amp Draw: 2.0 (120v)


Standard Equipment:

- Complete filter set
- 5 ft. 2-ply ribbed rubber hose
- 2" diameter inlet hose with quick connect rubber cuffs
- Digital graphic controls
- (4) Industrial grade vibration isolators
- Installation guide / Operations manual

Standard Filter Set:

- Single Set Combined cartridge filtration system
 - Pre-Filter:
 - 85% efficient MERV 11 panel filter
 - HEPA Filter:
 - 99.97% efficient @ 0.3 micron
 - Activated Carbon Gas / Odor filter:
 - Provides broad spectrum gas/odor control
- 100 % recyclable construction

TECHNICAL DATA




Combined Cartridge Filter System (DT-1)

Pre-Filter

HEPA Filter

Activated Carbon Filter



- Programmable via USB port pressure set points, blower speeds, and VOC detection
- High visibility LED display indicating blower speed, filter, and unit system status
- System Data logging: monitoring blower usage, filter service intervals accessed by USB port



FUMEX ACCESSORIES



Source Capture Hoods



FA122
1"x4" Rectangular Hood



FXA-127
Straight Nozzle



FXA-125
3" Bell-Mouth Hood



FA-125
2" Round Hood

Source Capture Arms



FXA-36-31
Stainless Steel Flexible Arm



A-28-2
2" Diameter Articulating Arm

